











# Pièces d'usure

Lames de coupe	<i>Page 2</i>
Bras hydraulique Boule de remorquage Stabiliseur de chaîne	<i>Page 3</i>
Pneus	<i>Page 4</i>
Divers	<i>Page 5</i>

### ROTARY TILLERS BLADES - KUBOTA

	Code	Description
	MA-713	<b>25x10 R=200 Curved</b>
	" -701	<b>Short 22X8 R=210mm</b>
	MA-711	<b>Short 22X8 L=210mm Cutted edge 6000</b>
	" -703	<b>Short 25X10 L=220mm</b>
	" -704	<b>Long 25X10 L=240mm</b>
	" -702	<b>Short 25X9 R=210mm Angle - side blade</b>
	" -730	<b>22" 10 Cutted edge 7001 R=210mm</b>
	" -708	<b>2 holes  R=240mm</b>

### ROTARY TILLERS BLADES

	Code	Description
	" -709	<b>Mini 22x6 R=150mm</b>
	MA-7-251	<b>24x7 200</b>
	MA-7-253	<b>22x7 190 Side blade</b>
	MA-7-252	<b>21x7 184</b>

### ROTARY TILLERS BLADES - HINOMOTO

	Code	Description
	MA-707	Hinomoto E 45\$ 6 <b>R=210mm</b>
	MA-717	Hinomoto N 40\$ 6 <b>R=210mm</b>

### ROTARY TILLERS BLADES -Mitsubishi, Yanmar

	Code	Description
	MA-721	<b>YM1100 20x8 10mm Hole R=200mm</b>
	" -720	<b>Mitsubishi Iseki 28x10 12.5mm hole L=210mm</b>
	" -722	<b>Iseki 34mmx9mm 12,5 Hole L=210mm</b>



### SPARE PARTS FOR JAPANESE TRACTOR

Code	Description
"\$-4001	<b>Kubota KIT,</b> Hydraulic Arms 50mmx12mm Length 500mm Top link (Hole –Hole) 430mm
"\$-4002	<b>Iseki KIT, Hydraulic Arms 50mmx12mm</b> Length 500mm Top link (Hole –Hole) 430mm
"\$-4003	<b>Kubota KIT, Hydraulic Arms</b> 50mmx16x Length 600mm Top link (Hole –Hole) 510



Code	Description
&( -7001	Top Link Base <b>Kubota</b>
&( -7003	Side base <b>Kubota 6000</b>
&( -7011	Top Link Base <b>Kubota</b> B1600 ZB1-16/17
&( -7013	*, - . / * 03. <b>Kubota</b> <b>B1600</b>
&( -7012	Base for Stabilizer Chain <b>1600</b> Right - Left



Code	Description
&( -7004	Draught connector <b>Kubota</b> <b>Adjustable</b>
&( -7005	Draught connector <b>Kubota</b> Fixed
&( -7006	Tow Ball Kubota
&( -7002	Top Link Base <b>ISEKI TS</b>
&( -7010	Top Link Base <b>YANMAR</b>
\$"-60- 26002	Draught connector SET 46 1301,1401 F14, F16

4



### TRACTOR TIRES High profile – Bridgestone Type

Type	profil	Diameter cm	Width cm	Application
5,00-10				
5-12	52	55	10	B6000
5.00-12	52	55	12	B7000/7001/1600/1400/1500
6-12		54	12	
6,00-12				Sial 193
5-14				
6-14	60	64	14.5	Kubota L1500, L2201
7-14	60	64	16	Front L1501,L2202 Rear B6000 B1200
7-16		70		Front L2601
8-16		77	23	Rear Kubota B1400,&7000, &7001
9,5-16		80	25	Rear B4200
8-18		80	23	Kubota B1500
8,3-20		84	23	Rear TU160, F16
8,3-22		92	23	Kubota L1500/1501.B1702 L2202MT1601
9,5-22				
8,3-24				
9,5-24				
11,2-24				
13,6-26				

### TRACTOR TIRES - Low profile

Type	profil	Diameter cm	Width cm	Application
4.00-9	43		8	Line 2" 4
4.00-12	41		8	Line 2" 4
5,00-15	63		10,5	Line 2" 4
5-15	61	64,5	11	Yanmar
6.00-12	57,5	60	15	
8-16				Kubota 1402, &7001
8-18				Rear Kubota B1500
8,3-20				Iseki TU160
8,3-24				
9.5-22				Kubota, L2202,L1-22
12.4-24				



Code	Description
\$"-206	Top Link , 19mm-19mm Min 22cm - Max 38 cm
TI-208	Adjustable leveling arm Kubota Min 40 cm – Max 52 cm Lower yoke hole 14mm Upper Ball hole 19mm
TI-207	Adjuster for stabilizer with 2 chain stabilizer Shackle 10 mm



Code	Description	HP
	Special Connection Kubota B7001,7000 Cross 23,8x61,3 Length 23,5cm	21
	Special Connection Iseki 35mm 6T x 28mm 6 T	21
	Special Connection Kubota No2 Cross 23,8x61,3 Length 24,5cm	21
TI-4-B1-10	L2202, L1-22 PTO 35mm 6T x 35mm 6T shaft 50cm spline shaft	25



#### BALLAST Kubota

Code	Description
\$"-34	Ballast with a assembly hole Thickness 5 cm ,Weight 17,5 kg